

BRUSHLESS DC REDUCTION MOTOR

上海吉茂电机有限公司

Square Box Type 60 Brushless DC Reduction Motor

25W 30W 40W ...

□60mm □70mm...

电机外形图 Motor Dimensions



Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Technical drawing of the motor showing dimensions and labels.

Rated power	Rated voltage	Rated current	Rated speed	Rated torque	Lead
W	V	A	RPM	N.m	mm
25	DC12	2.1	1800	0.13	60
30	DC24	1.9	1800	0.13	60
40	DC48	1.0	1800	0.13	60
50	DC24	2.0	2500	0.11	70
60	DC48	1.05	2500	0.11	70
75	DC24	2.2	3000	0.09	80
100	DC48	1.4	3000	0.09	80

Rated power	Rated voltage	Rated current	Rated speed	Rated torque	Lead
W	V	A	RPM	N.m	mm
120	DC24	2.5	3000	0.08	90
150	DC48	1.6	3000	0.08	90
200	DC24	3.0	3500	0.07	100
250	DC48	1.8	3500	0.07	100
300	DC24	3.5	4000	0.06	110
400	DC48	2.2	4000	0.06	110
500	DC24	4.0	4500	0.05	120
600	DC48	2.5	4500	0.05	120
800	DC24	5.0	5000	0.04	130
1000	DC48	3.0	5000	0.04	130
1200	DC24	6.0	5500	0.03	140
1500	DC48	3.5	5500	0.03	140
2000	DC24	8.0	6000	0.02	150
2500	DC48	4.5	6000	0.02	150
3000	DC24	10.0	6500	0.01	160
4000	DC48	6.0	6500	0.01	160
5000	DC24	12.0	7000	0.01	170
6000	DC48	7.0	7000	0.01	170
8000	DC24	16.0	7500	0.01	180
10000	DC48	10.0	7500	0.01	180